

FUNDERINGPARAMETERS - TRACK DOWN						
N°	Kolom	Detail	Peil P (m)	BOS (m)	B (mm)	H (mm)
1	TD1	B	42.219	42.259	1200	1200
2	TD1	B	42.219	42.259	1200	1200
3	TD1	E	42.219	42.259	1200	700
4	TD2	A	40.878	40.918	3300	3500
5	TD2	A	40.878	40.918	3300	700
6	TD2	E	40.878	40.918	1400	1400
7	TD3	B	41.732	41.772	2300	2300
8	TD3	B	41.732	41.772	2200	2200
9	TD3	E	41.732	41.772	1400	1400
10	TD4	B	41.120	41.160	1700	1700
11	TD4	B	41.120	41.160	2200	2200
12	TD4	C	41.120	41.160	3000	3000
13	TD4	E	41.120	41.160	2300	2300
14	TD5	B	40.936	40.976	2600	2600
15	TD5	B	40.936	40.976	2400	2400
16	TD5	D	40.936	40.976	2400	1000
17	TD6	B	41.478	41.518	1300	1300
18	TD6	B	41.478	41.518	1400	1400
19	TD6	E	41.478	41.518	1600	1200
20	TD7	B	41.778	41.818	1200	1200
21	TD7	B	41.778	41.818	1200	600
22	TD7	E	41.778	41.818	1300	700
23	TD8	B	41.767	41.807	1600	1600
24	TD8	B	41.767	41.807	1200	600
25	TD8	E	41.767	41.807	1500	1200
26	TD9	B	41.273	41.313	1800	1800
27	TD9	B	41.273	41.313	1400	600
28	TD9	E	41.273	41.313	1200	900
29	TD10	D	41.930	41.970	1200	1200
30	TD10	D	41.930	41.970	1200	600
31	TD10	E	41.930	41.970	1200	700
32	TD11	D	41.709	41.749	1200	600
33	TD11	D	41.709	41.749	1200	600
34	TD11	E	41.709	41.749	1200	800
35	TD12	D	40.787	40.827	1300	1300
36	TD12	D	40.787	40.827	1300	600
37	TD12	E	40.787	40.827	1200	900
38	TD13	D	39.756	39.796	1200	600
39	TD13	D	39.756	39.796	1200	600
40	TD14	D	39.423	39.463	1200	600
41	TD14	D	39.423	39.463	2200	600
42	TD14	E	39.423	39.463	4200	1200
43	TD15	D	39.003	39.043	1200	600
44	TD15	D	39.003	39.043	1200	600
45	TD15	E	39.003	39.043	1900	1000
46	TD16	D	39.701	39.741	1200	600
47	TD16	D	39.701	39.741	1200	600
48	TD17	D	39.536	39.576	1200	600
49	TD17	D	39.536	39.576	1200	600
50	TD18	D	40.259	40.299	1200	600
51	TD18	D	40.259	40.299	1200	600
52	TD19	D	40.833	40.873	1200	600
53	TD19	D	40.833	40.873	1200	700
54	TD19	E	40.833	40.873	1200	600
55	TD20	D	41.325	41.365	2400	600
56	TD20	D	41.325	41.365	1200	600
57	TD21	D	41.233	41.273	1200	600
58	TD21	D	41.233	41.273	1200	600
59	TD21	E	41.233	41.273	1200	1000
60	TD22	D	40.654	40.694	1200	600
61	TD22	D	40.654	40.694	1200	600
62	TD23	E	40.583	40.623	1200	600
63	TD23	E	40.583	40.623	1200	600
64	TD24	E	40.647	40.687	1200	600
65	TD24	E	40.647	40.687	1200	600
66	TD25	E	40.400	40.440	1200	600
67	TD25	E	40.400	40.440	1200	600

FUNDERINGPARAMETERS - TRACK UP						
N°	Kolom	Detail	Peil P (m)	BOS (m)	B (mm)	H (mm)
68	TU1	J	39.711	39.751	1600	2800
69	TU2	H	41.108	41.148	1200	600
70	TU2	H	41.108	41.148	1200	600
71	TU3	G	41.509	41.549	1200	600
72	TU3	G	41.509	41.549	1200	600
73	TU4	F	42.074	42.114	1200	600
74	TU4	F	42.074	42.114	1200	600
75	TU4	I	42.074	42.114	1200	600
76	TU5	F	42.806	42.846	2200	2200
77	TU5	F	42.806	42.846	2300	2300

FUNDERINGPARAMETERS - TOEGANGSHELLING						
N°	Kolom	Detail	Peil P (m)	BOS (m)	B (mm)	H (mm)
78	TH1	K	40.030	40.070	1300	1300
79	TH1	K	40.030	40.070	1300	600
80	TH2	L	40.092	40.107	1900	1100
81	TH2	L	40.857	40.862	2900	1100
82	TH3	M	40.878	40.888	3000	7500
83	TH3	---	40.878	40.878	1400	3109
84	TH3	M	40.878	40.888	2000	4750
84	TH3	O	40.878	40.918	2000	4750
85	TH4	M	41.756	41.766	600	9600
85	TH4	N	41.756	41.796	600	9600
86	TH5	M	41.750	41.760	600	9600
86	TH5	N	41.750	41.790	600	9600
87	TH6	M	42.113	42.123	600	9600
87	TH6	N	42.113	42.153	600	9600
88	TH7	M	42.691	42.701	600	9600
88	TH7	N	42.691	42.731	600	9600

FUNDERINGPARAMETERS - TOREN						
N°	Kolom	Detail	Peil P (m)	BOS (m)	B (mm)	H (mm)
89	TO1	P	42.510	42.580	3100	1300
90	TO2	P	42.510	42.580	3100	1300
91	TO3	P	42.510	42.580	3100	1300
92	TO4	P	42.510	42.580	3100	1300
93	LIFT	Q	42.550	42.620	5000	2300

FUNDERINGPARAMETERS - UTSTAPZONE						
N°	Kolom	Detail	Peil P (m)	BOS (m)	B (mm)	L (mm)
100	UZ1	HOLD	40.109	HOLD	1200	1200
101	UZ29	HOLD	40.232	HOLD	1300	1300
102	UZ30	HOLD	40.232	HOLD	1200	700
103	UZ2	HOLD	40.382	HOLD	1200	600
104	UZ3	HOLD	40.109	HOLD	1200	600
105	UZ4	HOLD	40.382	HOLD	1200	600
106	UZ5	HOLD	40.109	HOLD	1200	600
107	UZ6	HOLD	40.382	HOLD	1200	600
108	UZ7	HOLD	40.109	HOLD	1200	600
109	UZ8	HOLD	40.382	HOLD	1200	600
110	UZ9	HOLD	39.925	HOLD	1200	600
111	UZ10	HOLD	40.165	HOLD	1200	600
112	UZ11	HOLD	39.495	HOLD	1200	600
113	UZ12	HOLD	39.899	HOLD	1200	600
115	UZ13	HOLD	39.495	HOLD	1200	600
116	UZ14	HOLD	39.899	HOLD	1200	600
117	UZ15	HOLD	39.495	HOLD	1200	600
118	UZ16	HOLD	39.899	HOLD	1200	600
119	UZ17	HOLD	39.500	HOLD	1300	1300
120	STR3	HOLD	39.321	HOLD	1300	2400
120	UZ18	HOLD	39.321	HOLD	1300	2400
121	UZ19	HOLD	39.500	HOLD	1300	1300
122	UZ20	HOLD	39.500	HOLD	1300	1300
123	UZ21	HOLD	39.550	HOLD	1200	600
124	UZ22	HOLD	39.550	HOLD	1200	600
125	UZ23	HOLD	39.380	HOLD	1200	600
126	UZ24	HOLD	39.380	HOLD	1200	600
127	UZ25	HOLD	39.300	HOLD	1200	600
128	UZ26	HOLD	39.300	HOLD	1200	600
129	UZ27	HOLD	39.147	HOLD	600	4800
130	UZ28	HOLD	39.500	HOLD	150	22000
132	STR2	HOLD	39.321	HOLD	1400	1400
133	STR1	HOLD	39.321	HOLD	1200	1200
134	STR6	HOLD	39.321	HOLD	1200	1200
135	STR5	HOLD	39.321	HOLD	1400	1400
136	STR4	HOLD	39.321	HOLD	1200	600
137	BO11	HOLD	39.733	HOLD	600	8000
138	PUB1	HOLD	39.733	HOLD	600	2400
139	PUB2	HOLD	39.733	HOLD	600	2400

FUNDERINGPARAMETERS - TOEGANGSHELLING						
N°	Kolom	Detail	Peil P (m)	BOS (m)	B (mm)	L (mm)
100	UZ1	HOLD	40.109	HOLD	1200	1200
101	UZ29	HOLD	40.232	HOLD	1300	1300
102	UZ30	HOLD	40.232	HOLD	1200	700
103	UZ2	HOLD	40.382	HOLD	1200	600
104	UZ3	HOLD	40.109	HOLD	1200	600
105	UZ4	HOLD	40.382	HOLD	1200	600
106	UZ5	HOLD	40.109	HOLD	1200	600
107	UZ6	HOLD	40.382	HOLD	1200	600
108	UZ7	HOLD	40.109	HOLD	1200	600
109	UZ8	HOLD	40.382	HOLD	1200	600
110	UZ9	HOLD	39.925	HOLD	1200	600
111	UZ10	HOLD	40.165	HOLD	1200	600
112	UZ11	HOLD	39.495	HOLD	1200	600
113	UZ12	HOLD	39.899	HOLD	1200	600
115	UZ13	HOLD	39.495	HOLD	1200	600
116	UZ14	HOLD	39.899	HOLD	1200	600
117	UZ15	HOLD	39.495	HOLD	1200	600
118	UZ16	HOLD	39.899	HOLD	1200	600
119	UZ17	HOLD	39.500	HOLD	1300	1300
120	STR3	HOLD	39.321	HOLD	1300	2400
120	UZ18	HOLD	39.321	HOLD	1300	2400
121	UZ19	HOLD	39.500	HOLD	1300	1300
122	UZ20	HOLD	39.500	HOLD	1300	1300
123	UZ21	HOLD	39.550	HOLD	1200	600
124	UZ22	HOLD	39.550	HOLD	1200	600
125	UZ23	HOLD	39.380	HOLD	1200	600
126	UZ24	HOLD	39.380	HOLD	1200	600
127	UZ25	HOLD	39.300	HOLD	1200	600
128	UZ26	HOLD	39.300	HOLD	1200	600
129	UZ27	HOLD	39.147	HOLD	600	4800
130	UZ28	HOLD	39.500	HOLD	150	22000
132	STR2	HOLD	39.321	HOLD	1400	1400
133	STR1	HOLD	39.321	HOLD	1200	1200
134	STR6	HOLD	39.321	HOLD	1200	1200
135	STR5	HOLD	39.321	HOLD	1400	1400
136	STR4	HOLD	39.321	HOLD	1200	600
137	BO11	HOLD	39.733	HOLD	600	8000
138	PUB1	HOLD	39.733	HOLD	600	2400
139	PUB2	HOLD	39.733	HOLD	600	2400

FUNDERINGPARAMETERS - TOEGANGSHELLING						
N°	Kolom	Detail	Peil P (m)	BOS (m)	B (mm)	L (mm)
100	UZ1	HOLD	40.109	HOLD	1200	1200
101	UZ29	HOLD	40.232	HOLD	1300	1300
102	UZ30	HOLD	40.232	HOLD	1200	700
103	UZ2	HOLD	40.382	HOLD	1200	600
104	UZ3	HOLD	40.109	HOLD	1200	600
105	UZ4	HOLD	40.382	HOLD	1200	600
106	UZ5	HOLD	40.109	HOLD	1200	600
107	UZ6	HOLD	40.			