



Volgens		UITVOERINGSKLASSE	EXC 2
EN1090-2		OPPERVLAKTEBEH.	Zie kader
		STAALSOORT	S355 JR
		LASSEN	Tenzij anders vermeld
		WPS	0401, 0301
		BEVEST. MAT.	ELVZ 8.8

Samenstelling		C132		Aantal	1	1242.9	kg
Pos.	Profiel	Materiaal	Aantal	Lengte (mm)	Gewicht (kg)		
Cs132	PL20*2072	S355JR	1	2196	511.3		
Cs1016	PL8*649	S355JR	1	1089	9.9		
Cs1017	PL8*52	S355JR	1	85	0.3		
Cs1086	PL15*863	S355JR	1	1059	48.0		
Cs1087	PL15*866	S355JR	1	2096	96.0		
Cs1089	PL15*887	S355JR	1	1404	67.9		
Cs1090	PL15*887	S355JR	1	1750	84.7		
Cs1136	PL20*826	S355JR	1	1552	140.9		
Cs1137	PL20*732	S355JR	1	1312	113.4		
Cs1138	PL20*686	S355JR	1	1077	93.0		
Cs1152	PL5*618	S355JR	1	976	4.9		
Cs1153	PL5*115	S355JR	8	326	0.8		
Cs1154	PL5*115	S355JR	10	199	0.5		
Cs1160	STRIP5*60	S355JR	2	49	0.1		
Cs1161	STRIP5*60	S355JR	10	44	0.1		
Cs1162	STRIP5*60	S355JR	10	139	0.3		
Cs1163	STRIP5*60	S355JR	8	149	0.4		
Cs1183	PL5*96	S355JR	3	135	0.4		
Cs1207	PL10*366	S355JR	1	605	17.3		
Cs1208	PL10*368	S355JR	1	605	17.4		
Cs1209	PL10*370	S355JR	1	605	17.5		
Cs1210	_M12	S355JR	12	60	0.0		