



Volgens		LUITVOERINGSKLASSE	EXC 2
EN1090-2		OPPERVLAKTEBEH.	Zie kader
		STAALSOORT	S355 JR
		LASSEN	z. Tenzij anders vermeld
		WPS	9401-0301
		BEVEST. MAT.	ELI/2.8.8

  

Samenstelling C141				Aantal: 1	3844.5 kg
Pos.	Profiel	Materiaal	Aantal	Lengthe (mm)	Gewicht (kg)
Cs141	PL10*1880	S355JR	1	2040	301.1
Cs1001	PL8*135	S355JR	1	2156	18.3
Cs1002	PL8*169	S355JR	1	195	2.1
Cs1009	PL8*135	S355JR	1	2242	19.0
Cs1010	PL8*135	S355JR	1	1716	14.6
Cs1017	PL8*52	S355JR	7	85	0.3
Cs1019	PL15*374	S355JR	1	2461	108.3
Cs1020	PL15*374	S355JR	1	2210	97.3
Cs1021	PL15*374	S355JR	1	1691	74.5
Cs1026	PL15*260	S355JR	2	374	11.5
Cs1030	PL15*260	S355JR	2	394	12.1
Cs1031	PL15*372	S355JR	1	1880	82.3
Cs1037	PL15*394	S355JR	1	1666	77.3
Cs1038	PL15*394	S355JR	1	1938	89.9
Cs1041	PL15*394	S355JR	1	1275	59.1
Cs1042	PL15*394	S355JR	1	1483	68.8
Cs1091	PL20*604	S355JR	1	1802	169.6
Cs1092	PL20*1802	S355JR	1	1956	531.6
Cs1093	PL20*1735	S355JR	1	1970	488.2
Cs1096	PL20*604	S355JR	1	1675	156.8
Cs1097	PL20*621	S355JR	1	2077	201.2
Cs1098	PL20*621	S355JR	1	1470	137.6
Cs1099	PL20*621	S355JR	1	1984	176.7
Cs1100	PL20*621	S355JR	1	1526	147.6
Cs1158	STRIP5*60	S355JR	17	139	0.3
Cs1159	STRIP5*60	S355JR	1	266	0.6
Cs1163	STRIP5*60	S355JR	7	149	0.4
Cs1164	STRIP5*60	S355JR	17	115	0.3
Cs1168	STRIP5*60	S355JR	9	266	0.6
Cs1172	STRIP5*120	S355JR	1	2156	10.2
Cs1175	STRIP5*30	S355JR	2	50	0.1
Cs1180	PL5*175	S355JR	6	326	1.0
Cs1181	PL5*175	S355JR	13	199	0.7
Cs1185	PL5*95	S355JR	11	135	0.4
Cs1186	STRIP5*120	S355JR	1	169	0.8
Cs1187	PL5*141	S355JR	1	195	1.0
Cs1188	PL5*112	S355JR	1	156	0.5
Cs1193	STRIP5*120	S355JR	1	1740	8.2
Cs1194	STRIP5*120	S355JR	1	2273	10.7
Cs1198	PL10*394	S355JR	1	2040	63.1
Cs1199	PL10*623	S355JR	2	2040	99.2
Cs1200	PL10*609	S355JR	1	2040	96.9
Cs1201	PL10*394	S355JR	1	2040	63.1
Cs1202	PL10*404	S355JR	2	2040	64.7
Cs1203	PL10*414	S355JR	1	1880	61.1
Cs1204	PL10*374	S355JR	2	605	17.8
Cs1205	PL10*372	S355JR	3	605	17.7
Cs1210	M12	S355JR	33	60	0.0