



R-20-0012 BRINK GLMP Borghese Logis 18.05.2021 08:13:35

MERKENPOSTLIJST Merk: S136 lengte (mm): 22609
OPMERKING: zeeeg 75mm

Pos	Profiel	Materiaal	Aantal	Lengte (mm)	Omvolte (kg)
2501	KK120/5	S355JRH	1	2266	37,1
2502	KK120/5	S355JRH	1	2117	33,8
2600	HEB200	S355JR	1	10349	646,3
2601	KK160/8	S355JRH	1	10400	379,2
2602	KK105/5	S355JRH	1	2036	33,2
2603	KK100/4	S355JRH	1	2162	23,7
2604	KK100/4	S355JRH	1	2159	23,7
2605	KK100/4	S355JRH	1	2134	23,2
2606	KK160/8	S355JRH	1	11950	435,7
2607	KK100/4	S355JRH	1	2228	24,7
2608	KK100/4	S355JRH	1	2201	24,3
2609	KK100/4	S355JRH	1	2198	24,2
2610	KK100/4	S355JRH	1	2120	23,1
2611	KK100/4	S355JRH	1	2096	22,7
2613	KK110/5	S355JRH	1	1992	29,2
2602	FLAT101100	S355JR	2	180	5,2
2607	FLAT101100	S355JR	2	180	2,9
3043	FLAT191180	S355JR	2	500	21,6
3044	FL19195	S355JR	12	118	14,9
3099	FLAT191180	S355JR	2	500	21,6
3632	FLAT191250	S355JR 215	1	230	6,3
4329	FL201222	S355JR	1	460	16,3
4329	FL201222	S355JR	1	310	11,0
4347	FL191180	S355JR 215	1	180	4,3
4485	DRAAG_M09	S 8	19	100	4,3
S136	HEB200	S355JR	1	12200	761,9
Totaal per merk:				22604	

Naam	Stuks	Paraaf
Samensteller:		
Lasser:		
Gecontroleerd:		
Conservering: RAL7011		
Tekening Naam: SPANT_MET_ZEEG 75mm		
Opdrachtgever: GLMP Borghese Logis		
Projectnaam: GLMP Schiphol WH3 and WH4		
Bouwlocatie: Walravenlaan 1-5		
Lassen: volgens EN-ISO 3834 of EN-ISO 14554		
Staatkwaliteit: S355: dubbele hoeken a=0,5% (min. a=0) eenzijdig a=1,1% (max. in een rechte lijn)		
S355: platte, buis & rolprofielen S355: buisprofielen		
S355: FPB, 2H2 profielen		
Bouten: S 8, 10, 12, 16, 20, 24, 30, 36, 42, 48, 56, 64, 72, 80, 90, 100, 110, 125, 140, 160, 180, 200, 225, 250, 280, 315, 355, 400, 450, 500, 560, 630, 710, 800, 900, 1000, 1120, 1250, 1400, 1600, 1800, 2000, 2250, 2500, 2800, 3150, 3550, 4000, 4500, 5000, 5600, 6300, 7100, 8000, 9000, 10000		
Schalen: zie tekening		
Tekenning: A [S136]		