



Pos	Profil	Materiaal	Aantal	Lengte (mm)	Gewicht (kg)
1042	PL1634.8	S235JR	1	606	106.2
P1002	STRIP10*120	S235JR	1	899	6.9
P1003	STRIP10*120	S235JR	1	960	7.3
P1022	STRIP20*150	S235JR	1	851	20.4
P1137	CAP31	S235JR	562		15.4
P1138	STRIP10*160	S235JR	1	5607	74.2
P1139	STRIP10*160	S235JR	1	890	10.9
P1340	L70/8	S235JR	1	2231	18.4
P1343	L70/8	S235JR	1	2330	19.5
P1345	L70/8	S235JR	1	2333	19.5
P1346	L70/8	S235JR	1	632	4.8
P1347	L70/8	S235JR	2	660	10.3
P1348	L70/8	S235JR	2	740	11.7
P1349	L70/8	S235JR	2	692	13.0
P1350	L70/8	S235JR	2	880	14.1
P1351	L70/8	S235JR	2	940	15.1
P1352	L70/8	S235JR	1	890	5.2
P1353	L70/8	S235JR	1	2330	19.5
P1354	L70/8	S235JR	1	597	4.7
P1355	L70/8	S235JR	1	2333	19.5
P1356	L70/8	S235JR	1	597	4.7
P1357	L70/8	S235JR	1	2230	18.5
P1358	L70/8	S235JR	1	2232	18.5
P1359	L70/8	S235JR	1	632	4.8
P1360	L70/8	S235JR	1	597	4.7
P1361	L70/8	S235JR	1	597	4.7
P1362	L70/8	S235JR	1	2232	18.5
P1363	L70/8	S235JR	1	519	3.8
P1370	L70/8	S235JR	1	406	2.9
P1371	L70/8	S235JR	1	418	3.8
P1372	L70/8	S235JR	1	406	2.9
P1400	L70/8	S235JR	1	412	3.1
P1404	L70/8	S235JR	1	412	3.1
P1405	L70/8	S235JR	1	2071	17.2
P1406	L70/8	S235JR	1	690	5.2
P1407	L70/8	S235JR	1	484	3.8
P1408	L70/8	S235JR	1	484	3.8
P1409	L70/8	S235JR	1	483	3.7
P1410	L70/8	S235JR	1	483	3.7
P1411	L70/8	S235JR	1	2231	18.4
P1412	L70/8	S235JR	1	2071	17.2
P1513	L70/8	S235JR	1	2230	18.5
P1559	STRIP10*160	S235JR	1	2330	29.8
P1570	STRIP10*160	S235JR	1	2230	28.5
P1571	STRIP10*160	S235JR	1	2231	28.6

T0000

KLINKNAGELS EERST AAN ACHTERZIJDE HOEKLIJN OF STRIP LASSEN, DAARNA ALS GEHEEL AAN LIJFPLAAT